

87700881

Fire Research Information Services  
National Bureau of Standards  
Bldg. 225, Rm. A46  
Washington, D.C. 20234

# NATIONAL BUREAU OF STANDARDS REPORT

2003

QUARTERLY REPORT

ON

EVALUATION OF REFRACTORY QUALITIES OF CONCRETES FOR JET  
AIRCRAFT WARM UP, POWER CHECK, AND MAINTENANCE APRONS

REFERENCE FILE  
DO NOT REMOVE

by

W. L. Pendergast, R. A. Heindl, C. R. Enoch, R. A. Clevenger



U. S. DEPARTMENT OF COMMERCE  
NATIONAL BUREAU OF STANDARDS

U. S. DEPARTMENT OF COMMERCE

Charles Sawyer, *Secretary*

NATIONAL BUREAU OF STANDARDS

A. V. Astin, *Director*



## THE NATIONAL BUREAU OF STANDARDS

The scope of activities of the National Bureau of Standards is suggested in the following listing of the divisions and sections engaged in technical work. In general, each section is engaged in specialized research, development, and engineering in the field indicated by its title. A brief description of the activities, and of the resultant reports and publications, appears on the inside of the back cover of this report.

**Electricity.** Resistance Measurements. Inductance and Capacitance. Electrical Instruments. Magnetic Measurements. Applied Electricity. Electrochemistry.

**Optics and Metrology.** Photometry and Colorimetry. Optical Instruments. Photographic Technology. Length. Gage.

**Heat and Power.** Temperature Measurements. Thermodynamics. Cryogenics. Engines and Lubrication. Engine Fuels. Cryogenic Engineering.

**Atomic and Radiation Physics.** Spectroscopy. Radiometry. Mass Spectrometry. Solid State Physics. Electron Physics. Atomic Physics. Neutron Measurements. Infrared Spectroscopy. Nuclear Physics. Radioactivity. X-Rays. Betatron. Nucleonic Instrumentation. Radiological Equipment. Atomic Energy Commission Instruments Branch.

**Chemistry.** Organic Coatings. Surface Chemistry. Organic Chemistry. Analytical Chemistry. Inorganic Chemistry. Electrodeposition. Gas Chemistry. Physical Chemistry. Thermochemistry. Spectrochemistry. Pure Substances.

**Mechanics.** Sound. Mechanical Instruments. Aerodynamics. Engineering Mechanics. Hydraulics. Mass. Capacity, Density, and Fluid Meters.

**Organic and Fibrous Materials.** Rubber. Textiles. Paper. Leather. Testing and Specifications. Polymer Structure. Organic Plastics. Dental Research.

**Metallurgy.** Thermal Metallurgy. Chemical Metallurgy. Mechanical Metallurgy. Corrosion.

**Mineral Products.** Porcelain and Pottery. Glass. Refractories. Enameled Metals. Concreting Materials. Constitution and Microstructure. Chemistry of Mineral Products.

**Building Technology.** Structural Engineering. Fire Protection. Heating and Air Conditioning. Floor, Roof, and Wall Coverings. Codes and Specifications.

**Applied Mathematics.** Numerical Analysis. Computation. Statistical Engineering. Machine Development.

**Electronics.** Engineering Electronics. Electron Tubes. Electronic Computers. Electronic Instrumentation.

**Radio Propagation.** Upper Atmosphere Research. Ionospheric Research. Regular Propagation Services. Frequency Utilization Research. Tropospheric Propagation Research. High Frequency Standards. Microwave Standards.

**Ordnance Development.** These three divisions are engaged in a broad program of research and development in advanced ordnance. Activities include basic and applied research, engineering, pilot production, field testing, and evaluation of a wide variety of ordnance matériel. Special skills and facilities of other NBS divisions also contribute to this program. The activity is sponsored by the Department of Defense.

**Missile Development.** Missile research and development: engineering, dynamics, intelligence, instrumentation, evaluation. Combustion in jet engines. These activities are sponsored by the Department of Defense.

● Office of Basic Instrumentation

● Office of Weights and Measures.

# NATIONAL BUREAU OF STANDARDS REPORT

NBS PROJECT

NBS REPORT

0903-21-4428

September 30, 1952

2003

## QUARTERLY REPORT

ON

EVALUATION OF REFRACTORY QUALITIES OF CONCRETES FOR JET  
AIRCRAFT WARM UP, POWER CHECK, AND MAINTENANCE APRONS

by  
W. L. Pendergast, R. A. Heindl, C. R. Enoch, R. A. Clevenger  
Refractories Section  
Mineral Products Division

Sponsored by  
U. S. Naval Civil Engineering Research  
and Evaluation Laboratory, Construction  
Battalion Center, Port Hueneme, California

NBS File No. 9.3/1134-C



The publication, r  
unless permission  
25, D. C. Such p  
ically prepared if

Approved for public release by the  
Director of the National Institute of  
Standards and Technology (NIST)  
on October 9, 2015.

or in part, is prohibited  
Standards, Washington  
report has been specifi-  
report for its own use.



QUARTERLY REPORT  
ON  
EVALUATION OF REFRACTORY QUALITIES OF CONCRETES FOR JET  
AIRCRAFT WARM UP, POWER CHECK, AND MAINTENANCE APRONS

Technical Requirements

The concretes must be of sufficient workability to give a 2-inch slump when tested in accordance with ASTM Method Designation C143-39 [1]. They also must develop a flexural strength of 650 psi. The strength requirement refers to the concretes after a twenty-eight day curing period. Resistance to destruction when exposed to rapidly increasing and fluctuating temperatures is necessary. Notification of the requirements for the limits of the slump test and flexural strength were received too late for application to the experimental work included in this report.





## I. INTRODUCTION

The objective of the investigation is the evaluation of the physical properties and the determination of the suitability of concretes for jet aircraft warm up, power check, and maintenance aprons.

For this quarterly period the concretes were designed using portland cement with each of five aggregates.

## II. MATERIALS

Cements. The three types of cement\* selected for this investigation were North American Type II portland, Green Bay portland pozzolan, and Lumnite high alumina hydraulic. The quantity of portland and portland pozzolan cement already stored in waterproof drums was considered sufficient for current use. However, it was necessary to obtain an additional shipment of Lumnite cement because the stock of the previously stored material was practically depleted. This cement was subjected to the same physical and chemical tests\*\* that the first shipment received. The results of these analyses indicated some slight differences, but such differences would not be considered significant.

---

\* The same brands of cement were used in an earlier investigation in which light-weight aggregates were studied [2]

\*\* Made by the Mineral Products Division, Concreting Materials Section, National Bureau of Standards.





Aggregates. In the current work aggregates of a more dense type, namely, crushed building brick, raw flint clay, calcined flint clay, Bluestone, and olivine, are being used in designing the concretes.

A study of the properties of these aggregates indicated that such materials approach the properties of crushed stone and crushed sand. Since three of the dense aggregates are not marketed in the proper gradation that will produce a workable concrete, it was necessary to crush, grind, and screen them to the desired sizes.

The properties of the dense aggregates, previously reported [2] are again given in table 1. These properties of the aggregates are required in properly designing the concrete mixes.

Concretes. The data used in designing the various concrete mixes was obtained from publications by the Portland Cement Association [3] and the National Ready Mix Concrete Association [4].

Trial batches were calculated and mixed using each of the five aggregates with portland cement. The cement was varied from four and one-half to seven sacks per cubic yard. This variation in cement content was chosen in an effort to produce



Materials		Weight ft <sup>3</sup>	Bulk Specific Gravity S.S. Dry (c)	Water Absorption Percent by weight
Identifica- tion	Size	Jigged (b)		
Bluestone	Coarse	98.0	2.74	0.24
	Fine	113.0	2.64	1.06
Building Brick	Coarse	71.9	2.26	8.93
	Medium	70.3	2.27	9.60
	Fine	91.9	2.37	6.10
Flint-clay Calcined	Coarse	101.7	2.65	0.90
	Fine	101.3	2.65	0.80
Flint-clay Raw	Coarse	101.5	2.52	4.76
	Fine	95.0	2.50	5.03
Olivine	Coarse	146.7	2.97	3.20
	Fine	130.5	3.09	1.00
White Marsh Gravel Sand	Coarse	110.9	2.64	0.30
	Fine	112.0	2.63	0.30

(a) Indicates distribute and Concrete Aggregates,"  
ASTM Standards on

(b) Indicates bulking

(c) "S.S." Saturated



Table 1. Properties of Aggregates

Materials		Sieve Analysis											Fineness Modulus (a)	Unit Weight lbs/ft <sup>3</sup>		Bulk Specific Gravity S.S. Dry (c)	Water Absorption Percent by weight
Identifica- tion	Size	Amount passing U. S. Standard Sieve, percent by weight												Loose	Jigged (b)		
		1"	3/4"	1/2"	3/8"	Nos.											
		1"	3/4"	1/2"	3/8"	4	8	16	30	50	100	200					
Bluestone	Coarse	100.0	99.1	71.6	22.7	3.1	2.0	—	—	—	—	—	6.73	83.6	98.0	2.74	0.24
	Fine	—	—	—	100.0	99.3	79.6	50.7	26.7	11.5	3.7	11.3	3.28	99.8	113.0	2.64	1.06
Building Brick	Coarse	100.0	99.1	66.8	15.2	4.4	3.9	—	—	—	—	—	6.77	61.4	71.9	2.26	8.93
	Medium	—	—	100.0	98.3	16.5	5.4	4.3	—	—	—	—	5.75	60.5	70.3	2.27	9.60
	Fine	—	—	—	100.0	99.9	70.9	50.5	36.0	23.5	11.0	7.5	3.08	80.1	91.9	2.37	6.10
Flint-clay Calcined	Coarse	100.0	99.6	85.3	70.4	44.2	24.9	—	—	—	—	—	5.60	87.7	101.7	2.65	0.90
	Fine	—	—	—	100.0	75.1	38.0	20.2	10.6	5.2	1.8	0.9	4.49	89.4	101.3	2.65	0.80
Flint-clay Raw	Coarse	100.0	99.8	83.2	69.8	45.5	29.3	—	—	—	—	—	5.55	86.0	101.5	2.52	4.76
	Fine	—	—	—	100.0	76.3	37.3	20.1	10.2	4.6	1.5	1.9	4.50	80.9	95.0	2.50	5.03
Olivine	Coarse	—	100.0	85.3	70.9	54.3	45.6	—	—	—	—	—	5.29	124.8	146.7	2.97	3.20
	Fine	—	—	—	100.0	99.9	99.3	82.0	65.5	35.2	10.3	4.0	2.08	114.4	130.5	3.09	1.00
White Marsh Gravel Sand	Coarse	89.9	76.2	54.1	31.9	3.3	—	—	—	—	—	—	6.88	100.1	110.9	2.64	0.30
	Fine	—	—	—	100.0	97.9	8.00	64.9	49.5	22.0	4.1	1.2	2.82	100.4	112.0	2.63	0.30

(a) Indicatee distribution of sizes of aggregate as determined by ASTM method C125-43 "Standard Definitions of Terms Relating to Concrete and Concrete Aggregates," ASTM Standards on Mineral Aggregates, Concrete, and Nonbituminous Highway Materials, Sept. 1948, page 70.

(b) Indicates bulking or fitting together of various sizes of aggregates.

(c) "S.S." Saturated aggregate - Surface Dry.





a concrete of satisfactory workability and of the specified strength. If a designed mix did not have good workability additional trial mixes were prepared changing the aggregate gradation by increasing or decreasing the fine- to coarse ratio of the aggregate. Eighteen batches of concrete were mixed and a set of specimens of each mix were fabricated. Each set of specimens consisted of: three 6x12 inch cylinders, two 3x4x16 inch prisms, and one 24x24x2 1/2 inch slab. The 24-inch slab, after a partial set, received an additional delayed finishing with a steel trowel. All specimens were covered with wet burlap until the end of a 24-hour period. They were then removed from the molds, cured for six days in a fog room, stored at laboratory temperature and humidity for twenty-one days, and tested. A detailed description of the method of testing was given in a previous report [27]. The compositions of the concretes are given in table II.

### III. RESULTS

The results of tests of trial concrete batches are given in table II.

The slump results are not as accurate a measure of the workability when angular aggregates are used as they are in conventional concretes with rounded aggregates.



Laboratory Identifi- cation <u>a/</u>	Length t	Young's modulus of elasticity Dynamic Longitudinal	Linear shrinkage <u>c/</u>	Abrasion Loss
		Lbs/in <sup>2</sup> x 10 <sup>6</sup> <u>c/</u>	%	Gms.
P-O-1A		4.810	0.050	109
P-O-1B		4.471	0.167	210
P-O-1C		4.473	0.083	135
P-O-1D		5.199	0.070	62
P-B-1A <u>b/</u>		2.252	0.115	59
P-B-1B		1.736	0.335	—
P-B-1C		2.090	0.460	65
P-B-1D		2.480	0.115	64
P-B-1E		—	—	—
P-BS-1A		3.980	0.000	54
P-BS-1B		4.521	0.070	45
P-BS-1C		4.681	0.180	31
P-RC-1A		1.883	0.233	40
P-RC-1B		1.728	0.250	39
P-RC-1C		2.034	0.133	38
P-C-1A		2.649	0.000	71
P-C-1B		2.979	0.050	52
P-C-1C		4.379	0.016	43

a/ The firing Brick, BS=Bluestone, RC=Raw Flint Clay,  
C=Calci

b/ Cement

c/ Determini



Table II. Properties of Trial Concrete Mixes

Laboratory Identifi- cation <sup>a/</sup>	Proportions by weight cement to fine to coarse aggregate	Cement content	Vinsol resin by weight of cement	Water content	Air content	Slump of fresh concrete	Weight of fresh concrete	Weight of concrete after 7-day fog and 21-day R.T.	Compressive strength 6x12 in. cylinder	Strength weight ratio	Young's modulus of elasticity Dynamic Longitudinal	Linear shrinkage <sup>c/</sup>	Abrasion Loss
		Bags/yd <sup>3</sup> of concrete	%	Gals/yd <sup>3</sup> of concrete	%	Inches	Lb/ft <sup>3</sup>	Lbs/ft <sup>3</sup>	Lbs/in <sup>2</sup> <sup>c/</sup>		Lbs/in <sup>2</sup> x 10 <sup>6</sup> <sup>c/</sup>	%	Gms.
P-O-1A	1 : 1.1 : 4.6	6.3	0.02	46.7	1.7	3.75	163	162	3145	19.5	4.810	0.050	109
P-O-1B	1 : 0.9 : 5.4	5.9	do	39.3	3.8	4.00	164	162	2825	17.4	4.471	0.167	210
P-O-1C	1 : 0.8 : 4.4	6.2	do	39.0	3.9	3.25	164	162	3330	20.5	4.473	0.083	135
P-O-1D	1 : 0.6 : 3.4	6.7	do	37.2	3.8	3.50	164	163	4155	25.6	5.199	0.070	62
P-B-1A <sup>b/</sup>	1 : 3.6 : 0.9 : 0.8	4.6	0.02	60.7	9.4	1.00	119	110	1900	17.3	2.252	0.115	59
P-B-1B	1 : 1.7 : 1.3 : 2.0	5.1	do	55.7	8.1	0.00	124	114	1480	15.0	1.736	0.335	—
P-B-1C	1 : 1.5 : 1.1 : 1.7	5.9	do	55.7	7.9	0.25	124	117	2470	21.1	2.090	0.460	65
P-B-1D	1 : 1.2 : 0.9 : 1.4	6.7	do	60.0	7.9	1.50	123	121	3125	25.8	2.480	0.115	64
P-B-1E	1 : 1.7 : 1.0 : 1.5	5.8	0.015	54.5	6.5	0.00	127	—	—	—	—	—	—
P-BS-1A	1 : 2.8 : 3.4	5.1	0.02	37.3	7.1	3.75	140	137	2340	17.0	3.980	0.000	54
P-BS-1B	1 : 2.2 : 2.5	6.5	do	39.2	5.7	3.50	142	140	3130	22.4	4.521	0.070	45
P-BS-1C	1 : 2.0 : 2.3	7.0	do	40.0	5.2	3.00	143	142	3330	23.5	4.681	0.180	31
P-RC-1A	1 : 2.8 : 3.0	4.7	0.02	47.0	12.5	0.75	125	121	1665	13.8	1.883	0.233	40
P-RC-1B	1 : 2.3 : 2.5	5.5	do	46.8	12.7	1.00	128	120	1690	14.0	1.728	0.250	39
P-RC-1C	1 : 1.9 : 2.1	6.2	do	49.8	15.1	2.50	125	123	1980	16.1	2.034	0.133	38
P-C-1A	1 : 2.9 : 3.2	4.5	0.02	36.7	15.3	—	126	123	960	7.4	2.649	0.000	71
P-C-1B	1 : 2.4 : 2.6	5.8	do	35.4	11.5	—	133	124	1775	14.3	2.979	0.050	52
P-C-1C	1 : 2.0 : 2.2	7.0	0.01	37.8	8.1	0.50	138	134	2975	24.2	4.379	0.016	43

<sup>a/</sup> The first letter indicates the type of cement, namely, P=Portland; the second letter, or letters, indicate the type of aggregate, O=olivine, B=Building Brick, BS=Bluestone, RC=Raw Flint Clay, C=Calcined clay; the numerical, 1, indicates cured for 28 days; the letters A, B, C, D, E, indicate different cement contents.

<sup>b/</sup> Cement : Fine : Medium : Coarse

<sup>c/</sup> Determined after 28-day curing period.





With an increase of cement content and the ratio of fine- to coarse aggregate remaining unchanged ~~\*/~~ an increase in compressive strength was developed. The concretes that failed to develop the expected compressive strength have higher air contents than are normally desirable. The air content can be decreased by lowering the amount of the air-entraining agent (Vinsol resin). This, however, may effect the placement of a mix.

The resistance to abrasion of concretes designed with olivine as an aggregate was less than it was when any other of the five aggregates were used. The data thus far indicates that concretes designed with the raw or the calcined flint clay aggregates, although comparatively low in compressive strength, have a somewhat higher resistance to abrasion.

---

~~\*/~~

Does not apply to P-O-1A, P-B-1A and P-B-1E. The figures denoting the ratio were rounded off to the nearest one-tenth.



- [1] ASTM Standards on Mineral Aggregates, Concrete, and Nonbituminous Highway Materials, September, 1948. Slump Test for Consistency of Portland Cement Concrete, page 115.
- [2] National Bureau of Standards Report 1817.
- [3] Design and Control of Concrete Mixes, Ninth Edition.
- [4] The Proportioning of Concrete, A. T. Goldbeck and J. E. Gray, revised edition June, 1949.



## **THE NATIONAL BUREAU OF STANDARDS**

### **Functions and Activities**

The functions of the National Bureau of Standards are set forth in the Act of Congress, March 3, 1901, as amended by Congress in Public Law 619, 1950. These include the development and maintenance of the national standards of measurement and the provision of means and methods for making measurements consistent with these standards; the determination of physical constants and properties of materials; the development of methods and instruments for testing materials, devices, and structures; advisory services to Government Agencies on scientific and technical problems; invention and development of devices to serve special needs of the Government; and the development of standard practices, codes, and specifications. The work includes basic and applied research, development, engineering, instrumentation, testing, evaluation, calibration services, and various consultation and information services. A major portion of the Bureau's work is performed for other Government Agencies, particularly the Department of Defense and the Atomic Energy Commission. The scope of activities is suggested by the listing of divisions and sections on the inside of the front cover.

### **Reports and Publications**

The results of the Bureau's work take the form of either actual equipment and devices or published papers and reports. Reports are issued to the sponsoring agency of a particular project or program. Published papers appear either in the Bureau's own series of publications or in the journals of professional and scientific societies. The Bureau itself publishes three monthly periodicals, available from the Government Printing Office: The Journal of Research, which presents complete papers reporting technical investigations; the Technical News Bulletin, which presents summary and preliminary reports on work in progress; and Basic Radio Propagation Predictions, which provides data for determining the best frequencies to use for radio communications throughout the world. There are also five series of nonperiodical publications: The Applied Mathematics Series, Circulars, Handbooks, Building Materials and Structures Reports, and Miscellaneous Publications.

Information on the Bureau's publications can be found in NBS Circular 460, Publications of the National Bureau of Standards (\$1.00). Information on calibration services and fees can be found in NBS Circular 483, Testing by the National Bureau of Standards (25 cents). Both are available from the Government Printing Office. Inquiries regarding the Bureau's reports and publications should be addressed to the Office of Scientific Publications, National Bureau of Standards, Washington 25, D. C.

